


GDS-F-B-B25

GOODALL DURACRIMP FEMALE SWIVEL BSP



APPLICATION :

- Goodall DuraCrimp couplings are recommended as steam hose connections.
- These couplings are also widely used for air and water applications up to 1"ID.

PRESSURE AND TEMPERATURE:

Recommended for steam service up to 261 PSI (18 BAR) and 450°F (232°C) THREAD

According ISO 228-1:2000 (BSP)

MATERIAL :

Stainless Steel AISI 304 (w.nr. 1.4301)

RECOMMENDED HOSE ATTACHMENTS :

- Goodall Duracrimp Ferrules type F-GDS
- Safety hose clamps according EN14423

FEATURES :

- Advantages of assemblies crimped with Goodall DuraCrimp ferrules:
 - low profile and eliminate sharp edges from bolts to prevent injuries
 - □ 100 % safe and leak-free
 - □ Ergonomic: lighter and offer possibility to mount user-friendly Goodall steam handle
- Special design interlock groove locks the Goodall DuraCrimp ferrule into place for a superior permanent condition
- Goodall Inferno ISO6134 or Super Inferno assemblies with DuraCrimp fittings and ferrules pass the MIL-DTL-29210 test

TYPE: GDS-F-B-B25

Code	For hose ID		L		TH	LT		ID		SW	
	NB	inch	mm	inch		mm	inch	mm	inch	mm	inch
GDS-F-B-B25-1/2"	DN12	1/2"	83,1	3,72	1/2' BSP	20,5	0,81	9	0,35	22	0,87
GDS-F-B-B25-3/4"	DN20	3/4″	87,1	3,43	3/4' BSP	24,5	0,96	14	0,55	27	1,06
GDS-F-B-B25-1"	DN25	1″	88,1	3,47	1' BSP	25,5	1,00	20	0,79	36	1,42
GDS-F-B-B25-11/2"	DN40	1.1/2"	117,0	4,61	11/2' BSP	27,5	1,08	33	1,30	50	1,97
GDS-F-B-B25-2"	DN50	2″	122,0	4,80	2' BSP	28,5	1,12	44	1,73	60	2,36

All information contained on this datasheet is subject to change without prior notice. GOODALL MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, IN-CLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFOR-MANCE OR USAGE OF TRADE. Buyer/end-user is responsible for determining whether the Goodall product is fit for a particular purpose and suitable for buyer's/user's method of use or application. Failure to follow procedures for selection, installation, care, maintenance and storage of hoses may result in the hose's failure to perform properly and may result in damage to property and/or serious injury. Goodall or any of its affiliates or subsidiaries shall not be subject to and disclaims any obligations or liabilities (including but not limited to all consequential, incidental and contingent damages) arising from tort claims (including without limitation negligence and strict liability) or other theories of law.