



AIR KING

APPLICATION:

- Medium-duty compressed air hose for use in construction sites
- Robust construction that is kink-resistant but still flexible
- Developed for the transfer of high-temperature air
- May be used as a tough water transfer hose

TEMPERATURE RANGE:

- For air service only:
-40°F to +268°F
-40°C to +131°C

BURST PRESSURE:

- Minimum 4:1

MATERIAL TUBE:

- Extruded, smooth nitrile (NBR) compound
- Exceptional resistance to heat and oil

REINFORCEMENTS:

- Multiple high-tensile steel wire braids
- Braided with brass-plated wire for corrosion resistance

MATERIAL COVER:

- Yellow or black, smooth SBR compound
- Superior abrasion resistance
- Excellent weather and ozone resistance

BRANDING:

- Blue longitudinal mylar stripe: GOODALL[®] AIR KING • AIR • 500 PSI
- Embossed stripe: N2844 • AIR KING • 500 PSI MAX WP • 10001 • REFER TO INDUSTRY RECOMMENDATIONS FOR PROPER CARE & MAINTENANCE

STANDARD LENGTHS:

- 100'
- 30.5 meters

AIR KING

ID		OD		maximum working pressure		minimum bend radius		weight	
mm	inch	mm	inch	bar	psi	mm	inch	kg/m	lb./ft.
51.0	2	65.5	2.58	34	500	228.6	9.0	2.31	1.55
76.0	3	91.9	3.62	34	500	317.5	12.5	3.85	2.59

All data at 68° F / 20° C