



## MILKO SD LITE

MEETS FDA, BFR AND EU 10/2011, EC 1935/2004

### APPLICATION :

- Highly flexible suction and delivery hose for filling and discharging milk tankers
- Also suitable for conveying alcoholic and non-alcoholic beverages products
- Light and easy to handle
- Complying to multiple international regulation
- Easy to clean because of smooth tube
- ADI (Animal Derived Ingredient) Free
- Non marking abrasion resistant cover
- Improved ergonomics for operators
- Superior kink and crush resistance

### TEMPERATURE RANGE :

- 22°F to +185°F
- 30°C to +85°C
- Open end steam cleaning up to 130°C/266°F (max 30 minutes)

### BURST PRESSURE:

- Minimum 18 bar / 270 psi

### MATERIAL TUBE :

- Extruded, smooth, white NR rubber
- Complies to FDA, Bfr and EC 1935/2004 regulations
- ADI (Animal Derived Ingredient) free
- Excellent resistance to the most common cleaning agents

### REINFORCEMENTS :

- Spiral-plyed high tensile synthetic fabric
- Plastic helix
- Metal helix for 4" hosesize

### MATERIAL COVER :

- Blue NR rubber compound
- Smooth, non-marking cover
- Heat, abrasion, weather & ozone resistant

### BRANDING:

- White longitudinal Mylar stripe : GOODALL MILKO SD LITE - FOOD 6 BAR - 90PSI
- Embossed strip : GOODALL MILKO SD LITE - 90PSI (6BAR) - quarter/year

### STANDARD LENGTHS:

- 40 meter
- 131ft

### MILKO SD LITE

ID		OD		maximum working pressure		minimum burst pressure		Vacuum	minimum bend radius		weight	
mm	inch	mm	inch	bar	psi	bar	psi	%	mm	inch	kg/m	lb./ft.
38	1 1/2"	51	2.0	6	90	18	270	70	120	4.7	1,1	0.7
50	2"	63	2.5	6	90	18	270	70	150	5.9	1,39	0.9
51	2"	64	2.5	6	90	18	270	70	150	5.9	1,39	0.9
53	2,09"	66	2.6	6	90	18	270	70	160	6.3	1,41	0.9
63,5	2 1/2"	77,5	3.1	6	90	18	270	70	190	7.5	1,85	1.2
75	3"	90	3.5	6	90	18	270	70	230	9.1	2,25	1.5
76	3"	91	3.6	6	90	18	270	70	230	9.1	2,25	1.5
100	4"	116	4.6	6	90	18	270	90	300	11.8	4	2.7

Size tolerances according ISO1307



All information contained on this datasheet is subject to change without prior notice. GOODALL MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Buyer/end-user is responsible for determining whether the Goodall product is fit for a particular purpose and suitable for buyer's/user's method of use or application. Failure to follow procedures for selection, installation, care, maintenance and storage of hoses may result in the hose's failure to perform properly and may result in damage to property and/or serious injury. Goodall or any of its affiliates or subsidiaries shall not be subject to and disclaims any obligations or liabilities (including but not limited to all consequential, incidental and contingent damages) arising from tort claims (including without limitation negligence and strict liability) or other theories of law.