



NUTRALON SD LITE

MEETS FDA, BFR AND EC 1935/2004
REACH COMPLIANT



APPLICATION :

- Crush-proof suction and discharge hose for transfer of milk products, animal fat, vegetable oil, fruit juices and other food products
- For tank truck or in-plant service
- Suitable for alcohol 96% at 40°C (intermittent at 80°C - 30 minutes)
- Excellent flexibility
- Improved ergonomics for operators
- Superior kink and crush resistance
- Complying to multiple international regulations
- Easy to clean because of smooth tube
- ADI (Animal Derived Ingredient) Free
- Phthalate Free
- Non marking abrasion resistant cover

TEMPERATURE RANGE :

- -20 °C to 90 °C
- Open end steam cleaning up to 130°C (max 30 minutes)

BURST PRESSURE:

- Minimum 4:1

MATERIAL TUBE :

- Very smooth, mirror-like white **DuraFood** proprietary rubber compound
- Non-contaminating odourless and tasteless formulation
- Complies to the most stringent international food regulations
- Excellent resistance to fatty foods like animal fats and vegetable oils
- Does not propagate bacteria growth
- Excellent resistance to the most common cleaning agents

REINFORCEMENTS :

- Multiple high tensile and heat resistant textile reinforcement
- Embedded monofilament thermoplastic helix

MATERIAL COVER :

- Blue, CR blend rubber
- Superior abrasion, weather and ozone resistance
- Non marking cover
- Resistant to vegetable oils and animal fats

BRANDING:

- White and blue longitudinal stripe: GOODALL NUTRALON SD LITE • FOOD 17 BAR – 250 PSI
- Embossed stripe: GOODALL NUTRALON SD LITE • 17 BAR • quarter/year

NUTRALON SD LITE

ID	OD	maximum working pressure	minimum burst pressure	vacuum	minimum bend radius	weight
mm	mm	bar	bar	%	mm	kg/m
32.0	46.5	17	68	70	95.0	1.31
38.0	52.5	17	68	70	115.0	1.53
51.0	68	17	68	70	152.0	1.90
63.0	82.5	17	68	70	305.0	2.70
76.0	98	17	68	70	457.0	3.85

All data at 20°C



NUTRALON SD LITE • FOOD 17 BAR - 250 PSI



All information contained on this datasheet is subject to change without prior notice. ERIKS MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Buyer/end-user is responsible for determining whether the Goodall product is fit for a particular purpose and suitable for buyer's/user's method of use or application. Failure to follow procedures for selection, installation, care, maintenance and storage of hoses may result in the hose's failure to perform properly and may result in damage to property and/or serious injury. ERIKS or any of its affiliates or subsidiaries shall not be subject to and disclaims any obligations or liabilities (including but not limited to all consequential, incidental and contingent damages) arising from tort claims (including without limitation negligence and strict liability) or other theories of law.