

SOLID



APPLICATION :

- Flexible and robust multi-purpose hose for air and water in industry and construction sites

TEMPERATURE RANGE :

- -30°C to +70°C

BURST PRESSURE:

- 3:1

MATERIAL TUBE :

- Black, smooth synthetic SBR rubber
- Suitable for oil-laden air
- Extruded

REINFORCEMENTS :

- Polyester yarn, spiralled
- High tensile strength

MATERIAL COVER :

- Black, smooth synthetic SBR rubber compound
- Extruded
- Weather and ozone resistant

BRANDING:

- GOODALL SOLID 20BAR WP (size) MAX.70°C

STANDARD LENGTHS:

- Fixed coil lengths

SOLID

ID	OD	maximum working pressure	minimum burst pressure	minimum bend radius	weight
mm	mm	bar	bar	mm	kg/m
6	12	20	60	60	0,13
10	17	20	60	100	0,20
13	21	20	60	130	0,29
16	25	20	60	160	0,46
19	29	20	60	220	0,52
25	35	20	60	250	0,65

Size tolerances according ISO1307 All data at 20°C

Goodall **SOLID** • 20BAR WP 25 MM MAX.70°F

All information contained on this datasheet is subject to change without prior notice. GOODALL MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Buyer/end-user is responsible for determining whether the Goodall product is fit for a particular purpose and suitable for buyer's/user's method of use or application. Failure to follow procedures for selection, installation, care, maintenance and storage of hoses may result in the hose's failure to perform properly and may result in damage to property and/or serious injury. Goodall or any of its affiliates or subsidiaries shall not be subject to and disclaims any obligations or liabilities (including but not limited to all consequential, incidental and contingent damages) arising from tort claims (including without limitation negligence and strict liability) or other theories of law.