SUPER INFERNO



APPLICATION:

- High-pressure steam hose for saturated steam at 450°F/232°C
- Heavy-duty construction with a 20:1 burst pressure for increased user safety
- Superior performance life
- Longer service life and reduced downtime
- The best choice for steam when safety and performance are valuable

TEMPERATURE RANGE:

- -40°F to +450°F
- -40°C to +232°C

BURST PRESSURE:

■ Minimum 20:1

MATERIAL TUBE:

- Extruded smooth, premium proprietary chlorobutyl (CIIR) compound
- Specifically designed to resist pop-corning and blistering

REINFORCEMENTS:

- Multiple braids of high-tensile steel wire
- Braided with brass plated wire for corrosion resistance

MATERIAL COVER:

- Red abrasion and ozone resistant EPDM
- Pin-pricked
- Excellent abrasion, weather and ozone resistance

BRANDING:

- Black spiral stripe: GOODALL • SUPER INFERNO • STEAM 250 PSI 450°F
- Embossed stripe: N2861 • SUPER INFERNO • 450°F MAX TEMP • 250 PSI MAX WP • CAUTION TIGHTEN **CLAMPS BEFORE USING** • * • 10001 • REFER TO INDUSTRY **RECOMMENDATIONS**

STANDARD LENGTHS:

MAINTENANCE

• 100 feet, 30.5 meters

FOR PROPER CARE &

SUPER INFERNO

ID		OD		maximum working pressure		minimum burst pressure		minimum bend radius		weight	
mm	inch	mm	inch	bar	psi	bar	psi	mm	inch	kg/m	lb./ft.
19.0	3/4	32.3	1.27	17	250	68	1000	101.6	4.0	0.92	0.62
25.0	1	39.4	1.55	17	250	68	1000	127.0	5.0	1.32	0.89
51.0	2	71.4	2.81	17	250	68	1000	355.6	14.0	3.79	2.55
All data at 6	8°F/20°C										

SUPER INFERNO • STEAM 250 PSI 450 F





All information contained on this datasheet is subject to change without prior notice. GOODALL MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Buyer/end-user is responsible for determining whether the Goodall product is fit for a particular purpose and suitable for buyer's/user's method of use or application. Failure to follow procedures for selection, installation, care, maintenance and storage of hoses may result in the hose's failure to perform properly and may result in damage to property and/or serious injury. Goodall or any of its affiliates or subsidiaries shall not be subject to and disclaims any obligations or liabilities (including but not limited to all consequential, incidental and contingent damages) arising from tort claims (including without limitation negligence and strict liability) or other theories of law.