



## TANKER SD FLEXOLINE

7 BAR – 100 PSI

### APPLICATION :

- Lightweight suction and delivery hose for hydrocarbon fuels and mineral oils having an aromatic content of maximum 55% by volume
- Transfer hose used in tank truck and general industrial applications
- Classification grade  $\Omega$ /T: ideal for applications in which an electrical static charge can occur, the static charge can be safely conducted through the conductive hose wall (attention : the installation must be grounded)

### TEMPERATURE RANGE :

- -30°C to +82°C
- -22°F to +80°F

### BURST PRESSUR :

- Minimum 3:1

### MATERIAL TUB :

- Black NBR rubber compound
- Electrically conductive  $R < 10^6 \Omega$

### REINFORCEMENTS :

- High tensile spiral-plied textile cords
- Steel helix wire

### MATERIAL COVER :

- NBR/PVC rubber compound, black, electrically conductive  $R < 10^6 \Omega$
- Oil, abrasion, weather & ozone resistant

- Wrapped finish impression

### BRANDING :

- Yellow longitudinal Mylar stripe : GOODALL TANKER SD FLEXOLINE - OIL 7 BAR – 100 PSI /T
- Embossed strip : GOODALL TANKER SD FLEXOLINE – NBR – SD – 7 bar (100PSI) - $\Omega$ /T - quarter/yearr

### STANDARD LENGTHS :

- 61 meter
- 200ft

### TANKER SD FLEXOLINE

ID		OD		maximum working pressure		minimum burst pressure		vacuum	minimum bend radius		weight	
mm	inch	mm	inch	bar	psi	bar	psi	%	mm	inch	kg/m	lb./ft.
51,0	2	61	2.40	7	100	21	300	100	255	10.04	1,26	0.85
76,0	3	88	3.46	7	100	21	300	90	380	14.96	2,05	1.38
102,0	4	116	4.57	7	100	21	300	90	510	20.08	2,81	1.89
152,0	6	170	6.69	7	100	21	300	80	760	29.92	5,60	3.76

Size tolerances according ISO1307 All data at 68°F/20°C

**Goodall** TANKER SD FLEXOLINE • OIL 7 BAR - 100 PSI  $\Omega$ /T  

All information contained on this datasheet is subject to change without prior notice. GOODALL MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Buyer/end-user is responsible for determining whether the Goodall product is fit for a particular purpose and suitable for buyer's/user's method of use or application. Failure to follow procedures for selection, installation, care, maintenance and storage of hoses may result in the hose's failure to perform properly and may result in damage to property and/or serious injury. Goodall or any of its affiliates or subsidiaries shall not be subject to and disclaims any obligations or liabilities (including but not limited to all consequential, incidental and contingent damages) arising from tort claims (including without limitation negligence and strict liability) or other theories of law.