

ULTRAPRESS



APPLICATION :

- Robust air hose for heavy duty applications in heavy industry, construction and mining
- Suitable for air with oil traces and water

TEMPERATURE RANGE :

- -30°C to +85°C

BURST PRESSURE:

- 3,6:1

MATERIAL TUBE :

- Black, smooth synthetic NBR/SBR rubber
- Suitable for oil-laden air

REINFORCEMENTS :

- High tensile, spiral-plied textile cords

MATERIAL COVER :

- Yellow, SBR/EPDM rubber compound
- Smooth with cloth impression
- Abrasion, weather and ozone resistant

BRANDING:

- Yellow longitudinal Mylar stripe: GOODALL ULTRAPRESS - AIR 25BAR
- Embossed strip: GOODALL ULTRAPRESS – 25 bar WP

STANDARD LENGTHS:

- 40 meter

ULTRAPRESS

ID	OD	maximum working pressure	minimum burst pressure	minimum bend radius	weight
mm	mm	bar	bar	mm	kg/m
13	23	25	90	104	0,24
16	28	25	90	128	0,36
19	33	25	90	152	0,50
25	39	25	90	200	0,62
32	48	25	90	256	0,89
38	56	25	90	304	1,18
51	71	25	90	408	1,77

Size tolerances according ISO1307 All data at 68°F/20°C