



## VINTAGE SD LITE

MEETS FDA, EC1935/2004, ADI FREE  
REACH COMPLIANT

### APPLICATION :

- Flexible suction and discharge hose with tasteless and odorless EPDM tube for use in wineries, breweries and other food and beverage industries
- High resistant EPDM tube resistant against all common cleaning and sanitizing agents.
- High temperature resistance for open steam sterilization and cleaning (max 30 minutes at 266°F/130°C)
- Extremely good bending radius
- The special crush-proof design of the hose allows the hose to reshape after accidental compression

### TEMPERATURE RANGE :

- 40°C to 100°C
- 40°F to 212°F
- Open end steam cleaning up to 130°C/266°F (max 30 minutes)

### BURST PRESSURE:

- 3:1

### MATERIAL TUBE :

- White, mirror smooth EPDM rubber compound
- Non-contaminating formulation
- Complies to the most stringent international food regulations
- Does not propagate bacteria growth
- Excellent resistance to the most common cleaning agents

### REINFORCEMENTS :

- High tensile spiral-ply textile cords
- Monofilament helix

### MATERIAL COVER :

- Smooth, red EPDM compound
- Wrapped finish impression
- Very good abrasion, weather & ozone resistance

### BRANDING:

- White longitudinal Mylar stripe : GOODALL VINTAGE SD LITE • 10 BAR – 150 PSI
- Embossed strip : GOODALL VINTAGE SD LITE – FOOD – 10 bar - quarter/year

### STANDARD LENGTHS:

- 40 meter

## VINTAGE SD LITE

ID		OD		maximum working pressure		Vacuum	minimum burst pressure		minimum bend radius		weight	
NB	inch	mm	inch	bar	psi	%	bar	psi	mm	inch	kg/m	lb./ft.
19	1/4"	35	1.38	10	150	80	30	450	80	3.14	0,80	0.54
25	5/16"	41	1.61	10	150	80	30	450	100	3.93	0,95	0.64
38	3/8"	54	2.12	10	150	80	30	450	180	7.08	1,32	0.89
51	1/2"	67	2.63	10	150	70	30	450	250	9.84	1,73	1.16
63,5	5/8"	80,5	3.16	10	150	70	30	450	315	12.40	2,30	1.54
76	3/4"	94	3.70	10	150	70	30	450	380	14.96	2,63	1.77

Size tolerances according ISO1307

All data at 68°F/20°C

Goodall VINTAGE SD LITE • 10 BAR - 150 PSI



All information contained on this datasheet is subject to change without prior notice. GOODALL MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Buyer/end-user is responsible for determining whether the Goodall product is fit for a particular purpose and suitable for buyer's/user's method of use or application. Failure to follow procedures for selection, installation, care, maintenance and storage of hoses may result in the hose's failure to perform properly and may result in damage to property and/or serious injury. Goodall or any of its affiliates or subsidiaries shall not be subject to and disclaims any obligations or liabilities (including but not limited to all consequential, incidental and contingent damages) arising from tort claims (including without limitation negligence and strict liability) or other theories of law.